

سایز	I <sub>peak</sub>	I <sub>max</sub>	I <sub>nom</sub>	LIGHT Overload up to 144%		STANDARD Overload up to 168%		HEAVY Overload up to 210%		STRONG Overload up to 240%		مدل ساخت ایتالیا SINUS PENTA	ردیف
	A	A	A	KW	HP	KW	HP	KW	HP	KW	HP		
	کاربرد سبک (فن و پمپ)		کاربرد عمومی		کاربرد سنگین		کاربرد فوق سنگین						
Motor power 380-415Vac													
S05	30.0	25.0	16.5	7.5	10.0	7.5	10.0	7.5	10.0	5.5	7.5	0014 4T BA2K2	1
S12	43.0	36.0	30.0	15.0	20.0	15.0	20.0	11.0	15.0	9.2	12.5	0020 4T BA2K2	2
S12	58.0	48.0	41.0	22.0	30.0	18.5	25.0	15.0	20.0	11.0	15.0	0025 4T BA2K2	3
S12	67.0	56.0	41.0	22.0	30.0	22.0	30.0	18.5	25.0	15.0	20.0	0030 4T BA2K2	4
S12	76.0	63.0	57.0	30.0	40.0	25.0	35.0	22.0	30.0	18.5	25.0	0034 4T BA2K2	5
S15	88.0	80.0	72.0	37.0	50.0	30.0	40.0	25.0	35.0	22.0	30.0	0040 4T BA2K2	6
S15	115.0	96.0	80.0	45.0	60.0	37.0	50.0	30.0	40.0	25.0	35.0	0049 4T BA2K2	7
S20	134.0	112.0	88.0	50.0	70.0	45.0	60.0	37.0	50.0	30.0	40.0	0060 4T BA2K2	8
S20	142.0	118.0	103.0	55.0	75.0	55.0	75.0	45.0	60.0	32.0	45.0	0067 4T BA2K2	9
S20	186.0	155.0	135.0	75.0	100.0	75.0	100.0	55.0	75.0	45.0	60.0	0086 4T BA2K2	10
S30	240.0	200.0	180.0	100.0	135.0	90.0	125.0	75.0	100.0	55.0	75.0	0113 4T BA2K2	11
S30	324.0	270.0	215.0	120.0	165.0	110.0	150.0	90.0	125.0	75.0	100.0	0150 4T BA2K2	12
S30	324.0	290.0	240.0	132.0	180.0	132.0	180.0	110.0	150.0	90.0	125.0	0162 4T BA2K2	13
S41	408.0	340.0	300.0	160.0	220.0	160.0	220.0	132.0	180.0	110.0	150.0	0180 4T XA2K0	14
S41	504.0	420.0	345.0	200.0	270.0	200.0	270.0	150.0	200.0	132.0	180.0	0202 4T XA2K0	15

S41	552.0	460.0	375.0	220.0	300.0	220.0	300.0	185.0	250.0	150.0	200.0	0217 4T XA2K0	16
S41	672.0	560.0	425.0	250.0	340.0	250.0	340.0	200.0	270.0	160.0	220.0	0260 4T XA2K0	17
S51	720.0	600.0	480.0	280.0	380.0	280.0	380.0	220.0	300.0	185.0	250.0	0313 4T XA2K0	18
S51	792.0	680.0	550.0	315.0	430.0	315.0	430.0	250.0	340.0	200.0	270.0	0367 4T XA2K0	19
S51	1,020.0	850.0	680.0	400.0	550.0	400.0	550.0	315.0	430.0	280.0	380.0	0402 4T XA2K0	20